

**BINDER MICACEO CHIARO SINTETICO**
**Code**

KJA.1688

**Binder**

KJA.1688

**% by weight: Pigment/Binder**

VARIO

**Description**
**Recommended for**
**Specific Weight Kg/Lt**

1,25

**VOC (g/Lt) product ready to use Dir. 2004/42/CE**

IIA(I) (500)500

**°Gloss**

25-35

**Application T°C**

10-45

**Pot-Life 20°C**

N.A.

**Colour Code**



TUTTI I COLORI

**Application**

PENNELLO, SPRAY




Use graduated stick N.:


		10-25°C	25-35°C		By Vol.	By Weight	Vol. x Airles
	Product	KJA.1688	KJA.1688			100	
	Hardener						
	Hardener						
	Thinner	RDL.A111	RDL.A111			15-20	
	Viscosity (sF 4 20°C)						20-21

**BINDER MICACEO CHIARO SINTETICO**
**Code**
**KJA.1688**

**Conventional**
**Gravity Feed**
**Suction Feed Spray**
**HVLP**
**Airless**


1,7-1,8	1,8-2,0	N.A.	N.A.
3-4	4	N.A.	N.A.
2-3	2-3	N.A.	N.A.
5-10	5-10	N.A.	N.A.
15-30	15-30	N.A.	N.A.
18-24	18-24	N.A.	N.A.
n.a.	n.a.	N.A.	N.A.
n.a.	n.a.	N.A.	N.A.
30-40	30-40	30-40	N.A.
60-80	60-80		
5-6	5-6	5-6	


**Nozzle (mm)**
**Pression (bar)**
**N. of Passes**

**Flash off (min) at 20°C**
**Dust off (min) at 20°C**

**Drying Time at 20°C (h)**
**Drying Time at 60°C (h)**
**Drying Short IR (min x cm)**

**Dry microns per pass**
**Micron secchi (min \ max)**
**Theoretical yield (mq\lt) x 50**
**Sanding with Orbital**
**Polishing**

**Overpaintable with...**
**Max Time to overcoat at 20°C**
**Min Time to overpaint in 20°C**

**Store free from frost**

**Store in cool place**

**Protect from umidity**

**Use fresh air mask**