

## RESINA POLIESTERE LIQUIDA

<b>Code</b> KFS.R100	<b>Binder</b> <input style="width: 100%;" type="text"/>	<b>% by weight: Pigment/Binder</b> <input style="width: 100%;" type="text"/>
-------------------------	--	---

**Description**

Polyester Resin for repairing

**Recommended for**
**Specific Weight Kg/Lt**

1,069

**VOC (g/Lt) product ready to use Dir. 2004/42/CE**

IIB(b) (250)250

**°Gloss**
**Application T°C**

5-35

**Pot-Life 20°C**


15-20min

**Colour Code**



TRASPARENTE

**Application**

PENNELLO, RULLO



Use graduated stick N.:

		10-25°C	25-35°C		By Vol.	By Weight	Vol. x Airles
	Product	KFS.R100	KFS.R100			100	
	Hardener	MEK PEROX	MEK PEROX			3-5	
	Hardener						
	Thinner						
	Viscosity (sF 4 20°C)						

**RESINA POLIESTERE LIQUIDA**
**Code**
**KFS.R100**

**Conventional**

Gravity Feed

Suction Feed Spray

HVLP


Airless



Nozzle (mm)

Pression (bar)

N. of Passes



Flash off (min) at 20°C


Dust off (min) at 20°C



Drying Time at 20°C (h)

Drying Time at 60°C (h)

Drying Short IR (min x cm)



Dry microns per pass

Micron secchi (min \ max)

Theoretical yield (mq\lt) x 50

Gravity Feed	Suction Feed Spray	HVLP	Airless

**Sanding with Orbital**
**Polishing**
**Overpaintable with...**

Max Time to overcoat at 20°C


Min Time to overpaint in 20°C



Store free from frost



Store in cool place



Protect from umidity



Use fresh air mask