

## FIBERTIX

<b>Code</b>	<b>Binder</b>	<b>% by weight: Pigment/Binder</b>
KFS.1300		

**Description**

Fiberglass putty.  
Fast hardening and High restructuring power

**Recommended for**

To use as filler for body shops repairs of sheets. Suitable also for trucks and for industrial coatings( on Steel, Wood, Hard Plastic, Fiberglass)

**Specific Weight Kg/Lt**

1,45

**VOC (g/Lt) product ready to use Dir. 2004/42/CE**

IIB(b) (250)250

**°Gloss**
**Application T°C**

5-35

**Pot-Life 20°C**

3-6 min.

**Colour Code**



GIALLO

**Application**

SPATOLA




Use graduated stick N.:

		10-25°C	25-35°C		By Vol.	By Weight	Vol. x Airles
	Product	KFS.1300	KFS.1300			100	
	Hardener	PEROX	PEROX			2-3	
	Hardener						
	Thinner						
	Viscosity (sF 4 20°C)						


## FIBERTIX

**Code**
**KFS.1300**



Nozzle (mm)  
 Pression (bar)  
 N. of Passes



Flash off (min) at 20°C  
 Dust off (min) at 20°C



Drying Time at 20°C (h)  
 Drying Time at 60°C (h)  
 Drying Short IR (min x cm)



Dry microns per pass  
 Micron secchi (min \ max)  
 Theoretical yield (mq\lt) x 50

Conventional			
Gravity Feed	Suction Feed Spray	HVLP	Airless

### Sanding with Orbital



Dry Sanding first with P80 and then with P120 and P240

### Polishing



### Overpaintable with...


Max Time to overcoat at 20°C  
 Min Time to overpaint in 20°C



Store free from frost



Store in cool place



Protect from umidity



Use fresh air mask