

BINDER 1K POLYGRIP
Code

KJA.0150

Binder

KJA.0150

% by weight: Pigment/Binder

20 / 80

Description
Recommended for
Specific Weight Kg/Lt

1,5

VOC (g/Lt) product ready to use Dir. 2004/42/CE

II (A) i (500) 500

°Gloss

20-30

Application T°C

10-40

Pot-Life 20°C

n.a

Colour Code



TUTTI I COLORI

Application

Spray



Use graduated stick N.:


		10-25°C	25-35°C		By Vol.	By Weight	Vol. x Airles
	Product	KJA.0150	KJA.0150		4	100	
	Hardener				n.a.	n.a.	
	Hardener						
	Thinner	RDL.P333	RDL.P333		1	25	
	Viscosity (sF 4 20°C)				15-16	15-16	

BINDER 1K POLYGRIP
Code
KJA.0150

Conventional			
Gravity Feed	Suction Feed Spray	HVLP	Airless
1,4	1,4		
3	3		
2-3	2-3		
5-10	5-10		
10-15	10-15		
1-2	1-2		
20-30	20-30	20-30	
30-60	30-60		
6-7	6-7	6-7	




Nozzle (mm)
 Pression (bar)
 N. of Passes



Flash off (min) at 20°C
 Dust off (min) at 20°C



Drying Time at 20°C (h)
 Drying Time at 60°C (h)
 Drying Short IR (min x cm)



Dry microns per pass
 Micron secchi (min \ max)
 Theoretical yield (mq\lt) x 50

Sanding with Orbital
**Polishing**
**Overpaintable with...**


Max Time to overcoat at 20°C
 Min Time to overpaint in 20°C



Store free from frost



Store in cool place



Protect from umidity



Use fresh air mask