

**MW-80 LIGHT UNIV BIANCO/WHITE**
**Code**

KFS.1102

**Binder**

**% by weight: Pigment/Binder**

**Description**

Universal Polyester Light Putty/Stopper for paddle application. Excellent Sanding.

**Recommended for**

To use as filler for body shops repairs of sheets. Suitable also for trucks and for industrial coatings( on Steel, Wood, Hard Plastic, Fiberglass)

**Specific Weight Kg/Lt**

1,17

**VOC (g/Lt) product ready to use Dir. 2004/42/CE**

IIB(b) (250)250

**°Gloss**
**Application T°C**

5-35

**Pot-Life 20°C**

3-6 min.

**Colour Code**



BIANCO WHITE

**Application**

SPATOLA



Use graduated stick N.:


		10-25°C	25-35°C		By Vol.	By Weight	Vol. x Airles
	Product	KFS.1102	KFS.1102			100	
	Hardener	PEROX	PEROX			2-3	
	Hardener						
	Thinner						
	Viscosity (sF 4 20°C)						

**MW-80 LIGHT UNIV BIANCO/WHITE**
**Code**
**KFS.1102**

Conventional			
Gravity Feed	Suction Feed Spray	HVLP	Airless



Nozzle (mm)  
 Pression (bar)  
 N. of Passes



Flash off (min) at 20°C  
 Dust off (min) at 20°C



Drying Time at 20°C (h)  
 Drying Time at 60°C (h)  
 Drying Short IR (min x cm)



Dry microns per pass  
 Micron secchi (min \ max)  
 Theoretical yield (mq\lt) x 50

**Sanding with Orbital**


Dry Sanding first with P80-P120 and then with P180

**Polishing**

**Overpaintable with...**


Max Time to overcoat at 20°C  
 Min Time to overpaint in 20°C



Store free from frost



Store in cool place



Protect from umidity



Use fresh air mask